



MOHAWK MATERIALS CO., INC.

Safety Data Sheet *Sand Mix*

Section 1 Product Name

Sand Mix

Section 2 Manufacturer

Company Information

Tulsa/Sand Springs Division; PO Box 640 Sand Springs, OK 74063; (918) 584-2707; (918) 584-2708 Fax; (800) 259-8721 Toll Free

Handi Sak Division; 8300 NW 3rd Oklahoma City, OK 73127; (405) 789-3001; (405) 789-3008 Fax; (800) 299-5228 Toll Free

Section 3 Product Description

Mohawk Materials Sand Mix is ideal for patching and leveling concrete surfaces. Sand Mix is perfect as a bedding layer for flagstone or brick pavers, or as an overlay over existing concrete. It is specifically designed for any job requiring concrete applications less than 2" thick.'

BASIC USE:

Recommended for construction or repairing of old concrete surfaces:

- Patching
- Leveling
- Overlayment
- Slabs
- Steps
- Pavers

COMPOSITION & MATERIALS:

Mohawk Materials Sand Mix is a uniformly blended mixture of Portland cement, sand and other approved ingredients designed for general concrete repairs.

Section 4 Advantages/Benefits

Mohawk Materials Sand Mix has several advantages including:

- High durability and impact resistant
- Easy to finish and cure
- Uniform aggregate sizes ensure easier mixing
- Thoroughly pre-blended mixture requires no dry mixing

Section 5 Preparation

Remove all broken and loose concrete or foreign materials from the surface area to be repaired. Clean the surface thoroughly. Use a pressure washer to clean the surface for best results. Coat the moistened and damaged surface with Mohawk Materials Bonding & Fortifier Admixture and allow to dry prior to overlay of Sand Mix.

Section 6 Mixing Instructions

Pour Sand Mix into a wet mixing container. Add water slowly, mixing thoroughly until sand mix reaches a 'plastic-like consistency. Avoid a 'soupy' mix too much water will weaken the concrete. For 1/2" to 1" thick repairs, substitute part of the mixing water with Mohawk Materials Bonding & Fortifier Admixture as an additive to improve bonding.

For large projects a concrete mixer is recommended. If a mixer is used, mix dry contents thoroughly with water for 5 minutes to achieve 'plastic-like' consistency.

Section 7 Placement

Use a trowel to work the Sand Mix into the repair area. Apply additional sand mix as needed to build up surface to desired thickness. Level and smooth the surface using a steel trowel for a smooth finish. If a rougher finish is desired, use a broom or wooden float.

Section 8 Curing

For proper curing keep the new surface covered and damp for five to seven days after patching and repair or simply apply Mohawk Materials Cure & Seal by spraying or rolling after the concrete surface has hardened but is still damp. If Mohawk Materials Cure & Seal is applied to the new surface then covering is not needed. (Note: Mohawk Materials Cure & Seal is not recommended for use under cold weather conditions.)

Properly moistened and cured concrete is stronger than air cured concrete. After concrete has cured, remove forms.

In cold weather, use warm water and protect concrete from freezing for at least 48 hours using plastic sheeting and insulation blankets if temperatures are expected to fall below 32 degrees F.

Section 9 Technical Information

ASTM Specifications:

Meets requirements of ASTM C387 specifications when used as directed.

Compressive Strength:

7 days 3,000 psi (20.7 Mpa)
28 days 5,000 psi (34.5 Mpa)

Section 10 Limitations

Adhering to recommended water additions is very important. Exceeding the maximum recommended water content per bag will result in inferior physical properties.

Sand Mix will not bond well to wood, asphalt, or any other foreign substances.

A bonding agent such as Mohawk Materials Bonding & Fortifier Admixture is recommended for maximum adhesion to old concrete surfaces.

For applications of 2" or thicker, use Mohawk Materials Concrete Mix.

Do not place when temperatures are below 40 degrees F. In cold weather, use warm water and protect from freezing for 48 hours.

Section 11 Coverage

One 80 lb bag (36.29 kg) yields approximately 2/3 cubic feet.

2/3 cu. Ft.	80 lb bag (36.29 kg)
1/2 cu. Ft.	60 lb bag (27.22 kg)
1/12 cu. Ft.	10 lb box (4.54 kg)

Section 12 Warning

Mohawk Materials Sand Mix contains Portland cement and sand. Normal safety wear such as protective clothing, boots, rubber gloves, dust masks, eye safety glasses should be worn while handling cement-based products. Material Safety Data Sheets are available up on request or at www.mohawkmaterials.com.

Section 13 Limited Warranty

This product meets or exceeds applicable ASTM C387 standards in force at the time of packaging. Packager, having no control over the use of the material, does not guarantee finished work. Replacement of any defective product or refund of the purchase price of defective product shall be the buyer's sole remedy under this warranty.

THIS LIMITED WARRANTY EXCLUDES ANY LIABILITY FOR ANY CONSEQUENTIAL, INCIDENTAL, INDIRECT OR SPECIAL DAMAGES.

EXCEPT FOR THE LIMITED WARRANTY MADE ABOVE. PACKAGER SPECIFICALLY DISCLAIMS AND EXCLUDES ANY OTHER EXPRESS WARRANTY, ANY IMPLIED WARRANTY OF MERCHANTABILITY OF GOODS AND ANY IMPLIED WARRANTY OF FITNESS OF GOODS FOR ANY PARTICULAR PURPOSE.

Mohawk Materials reserves the right to change specifications without notice.